

US006782437B2

(12) United States Patent Petty

(10) Patent No.: US 6,782,437 B2

(45) **Date of Patent:** Aug. 24, 2004

(54) METHOD OF COMMUNICATING ON A NETWORK

(75) Inventor: William K. Petty, Colorado Springs,

CO (US)

(73) Assignee: LSI Logic Corporation, Milpitas, CA

(US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 10/298,343

(22) Filed: Nov. 14, 2002

(65) Prior Publication Data

US 2003/0070017 A1 Apr. 10, 2003

Related U.S. Application Data

(62)	Division	of	application	No.	09/431,606,	filed	on	Nov.	1,
	1999.								

(51)	Int. Cl. ⁷	 G06F	13/0	0
(DI)	mu. Ci.	 GUOL	13/0	J

(56) References Cited

U.S. PATENT DOCUMENTS

4,920,339 A * 4/1990 Friend et al. 340/825.52

5,745,493	Α	*	4/1998	St. Clair 370/438
5,926,031	A	*	7/1999	Wallace et al 326/30
6,233,625	B1	*	5/2001	Vander Kamp et al 710/10
RE37,613	Ε	*	3/2002	Savage
6,438,624	B 1	*	8/2002	Ku et al 710/9

OTHER PUBLICATIONS

Small Computer System Interface—2 (SCSI—2), pp. 30–32, 40–41, 154–155, 390–391.*

Primary Examiner—Tim Vo

(74) Attorney, Agent, or Firm—Cochran, Freund and Young, LLC

(57) ABSTRACT

A method for communicating on a SCSI bus permits outof-band addressing and communication for normally nonaddressable devices such as SCSI expanders and terminators. The method remaps 18 SCSI data lines for out-of-band
operation and manipulates no more than those data lines.
Some of the data lines are remapped for purposes of outof-band signaling and data transfers. Advantageously,
manipulation of only the SCSI data lines prevents the
possible response of a device on the SCSI network that does
not support the out-of-band operations. Accordingly, the
disclosed method is backward compatible with existing
SCSI networks while allowing implementation of devices
having the increased functionality of out-of-band communication.

9 Claims, 10 Drawing Sheets

					<i>7</i>				
BIT	SP0	SD7	SD6	SD5	SD4	SD3	SD2	SD1	SD0
Function	Res	Res	Res	Res	RXER	OBSL	SEND	TSTB	нѕтв
						- 19	-12 -1	1 1	0 5
BIT	SP1	SD15	\$D14	SD13	SD12	SD11	SD10	SD9	SD8
Function	Res	Data Byte							

^{*} cited by examiner